




### COMPOUNDS

Greaselike materials composed of silicone fluids and silica fillers. Used for their sealing, dielectric, nonmetal-to-metal lubricating properties.



### DISPERSIONS

Finely divided solid lubricants suspended in lubricating fluid; preferred when it is necessary to apply lubricants in liquid form.



### ANTI-FRICTION COATINGS

"Lubricating paints"; when applied, these materials cure to form dry, solid lubricant coatings that are bonded to the surface.

## MOLYKOTE®

### Learn more

MOLYKOTE® lubricants are available through a distributor network of more than 3,000 distributors worldwide. And MOLYKOTE® has Lubricant Expertise Centers strategically located globally to provide you with expert technical service and support.

Our specialty lubricants include greases, anti-seize pastes, multipurpose oils, specialty compounds, dispersions, anti-friction coatings and more. Learn more about our extensive product and service offering by visiting [molykote.com](http://molykote.com).



### Contact us

#### Asia Pacific

Shanghai, China  
Mumbai, India

400 885 1888  
+18004190899

#### Europe, Middle East, Africa (EMEA)

Mechelen, Belgium

+800 3876 6838

#### Latin America

Barueri, Brazil  
Buenos Aires, Argentina  
Mexico City, Mexico

+55 (11) 0800 171715  
+0800 333 8766  
+01800 849 7514

#### North America

Midland, Michigan, USA  
& Wilmington, Delaware, USA

+1 833 338 7668 (U.S.)  
+1 800 387 2122 (Canada)



DuPont™, the DuPont Oval Logo, and all products, unless otherwise noted, denoted with ™, SM or ® are trademarks, service marks or registered trademarks of affiliates of DuPont de Nemours, Inc. © 2019 DuPont de Nemours, Inc. All rights reserved.

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable and falls within the normal range of properties. It is intended for use by persons having technical skill, at their own discretion and risk. This data should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.

(7/19) AGP16042M-14



### GREASES

Solid to semisolid materials consisting of a lubricating fluid, thickening agent and additives. Used on rolling element bearings and other moving parts.



### PASTES

Greaselike materials containing a very high percentage of solid lubricants. Used for assembly and lubrication of highly loaded, slow-moving parts or threaded fasteners.



### OILS

These lubricating fluids are fortified with carefully selected additives to provide optimum performance and service life while maximizing protection of the equipment and machinery they are designed to lubricate.

# This is MOLYKOTE®

## Specialty lubricants



Greases | Pastes | Oils | Compounds | Dispersions | Anti-Friction Coatings

High temp, high load, water resistance, high speed, food machinery, low noise, low temp

Prevention of stress corrosion cracking, solder embrittlement, fatigue and pitting; water resistance; constant coefficient of friction

Refrigeration, viscosity, oxidation stability, process gas oils, flush fluids, coupling fluids, barrier seal fluids, temperature stability

\*\*Contact your MOLYKOTE® distributor or sales representative to explore the complete MOLYKOTE® product line and identify the solution that best meets your needs.

- BR2 Plus** Heavy-duty black grease w/MoS<sub>2</sub> and other solid lubricants for general applications
- G-4700** Long-lasting synthetic black grease w/MoS<sub>2</sub> and other solid lubricants for heavier loads, extreme pressures and wider temperature applications than BR2 Plus
- G-4500** White, food grade NSF H1 grease, long-term synthetic w/solid lubricants for general applications w/moderate loads and high speeds
- G-1502FM** White, very tacky, food grade NSF H1 grease, long-term synthetic w/higher levels of solid lubricants for demanding applications w/high loads
- BG-20** High-speed bearing grease
- 33 Medium** Low-temp silicone grease
- 44 Medium** High-temp silicone grease
- 3451** Chemical-resistant grease
- 1292** Chemical-resistant grease particularly suitable for long-term lubrication


- 1000 Paste** Threaded connections, general use
- P-37 Paste** Threaded connections, high temperature, high alloys
- G-N Plus** Assembly and running-in
- DX Paste** Fretting (high-frequency vibration) between contracting/mating parts, nonstaining
- P-1900** Threaded connections and mechanical parts in food machinery industry
- P-40** Metal-free paste for mechanical components and threaded connections in offshore environment

- L-1122 & L-1122FM** Gearboxes, standard industrial (spur, helical, bevel) synthetic PAO, ISO 220 viscosity grade
- L-1146 & L-1146FM** Gearboxes, worm drive industrial synthetic PAO, ISO 460 viscosity grade
- L-1468FM** Chain oil synthetic PAO, ISO 68 viscosity grade
- L-1346FM** Hydraulic oil synthetic PAO, ISO 46 viscosity grade
- L-4611** Reciprocating compressor oil synthetic diester, ISO 100 viscosity grade
- L-1246** Rotary screw compressor oil synthetic PAO, ISO 46 viscosity grade
- L-1668FM** Rotary vane vacuum pump oil synthetic PAO blend, ISO 68 viscosity grade

\*For these applications, the products listed are the most commonly used in this subset of the complete MOLYKOTE® product line.

# Smart Lubrication™ solutions

More than 70 years of trusted expertise



Greases | Pastes | Oils | Compounds | Dispersions | Anti-Friction Coatings

For more information, visit us at [molykote.com](http://molykote.com) or contact your MOLYKOTE® distributor or sales representative.

Follow us on Twitter: [@molykote](https://twitter.com/molykote)

- 4 Compound** Electrical insulating compound
- 111 Compound** Valve lube and sealant, static O-ring lube w/specific specifications/approvals
- 55 O-Ring Grease** O-ring lubricant, dynamic applications
- G-804** Valve lube and sealant, static O-ring lube
- 340 Heat Sink** Thermally conductive compound

- Separator Spray** Silicone release agent and lubricant
- M-30 Dispersion** Chains and rollers of conveyor belts
- Metalform** Transparent wax solution for forming operations on metals

- D-321R** Air cure, dry film, higher loads, low coefficient of friction
- 3402-C LF** Air cure, dry film, high loads w/enhanced corrosion protection
- D-7409** Heat cure, higher durability than air cure

\*For these applications, the products listed are the most commonly used in this subset of the complete MOLYKOTE® product line.

High-current electricity, heat transfer, vacuum sealing, shear stability

Food contact/release, metal protection, solid lube additives, extreme temperature chains, low temp, gear oil additives

Coefficient of friction, load, color/transparent, durability, water-based, flexibility

\*\*Contact your MOLYKOTE® distributor or sales representative to explore the complete MOLYKOTE® product line and identify the solution that best meets your needs.