

# Pro Pump Hand Held Dispenser

Item No. 2564842

## PRODUCT DESCRIPTION

The Loctite® Pro Pump Hand Held Dispenser is a bottle-mounted adhesive dispenser that can be used with 50ml or 250ml bottles of Loctite anaerobic adhesives creating a complete dispensing system. This dispenser utilizes patented progressive cavity pump technology that is specifically designed to dispense Loctite® anaerobic threadlockers and retaining compounds. The ergonomic design allows the user to deliver a drop of adhesive with a single pull of the trigger. The multi-position nozzle delivers adhesive in three different orientations, horizontal, 45° up and 45° down and can also be folded down 90° for storage. The Loctite® Pro Pump Hand Held Dispenser enables more accurate and consistent application while eliminating waste and mess.



## Product Features

- No assembly required
- Compatible with all LOCTITE Anaerobic Threadlockers and Retaining Compounds
- Fits on both 50ml and 250ml Loctite® adhesive bottles (no additional parts needed)
- Articulating nozzle with slip luer feature for dispense tips
- Average dispense volume = 30 mg

## Benefits

- Easy to setup and easy to use
- Eliminates spills, waste, and mess
- Can be used to apply to difficult to reach blind holes
- Provides precise drop placement

### Technical Data:

- Total weight: 78 grams (2.8 oz)
- Size: Height = 115mm [4.0"], Width = 40mm [1.6"], Length = 115mm [4.6"]
- Viscosity Range: 1 to 15,000 mPas
- Wetted Components: POM, HDPE, AFLAS, Silicone
- Fluid Compatibility: Anaerobic Adhesive



### Items Supplied:

- Loctite® Pro Pump Hand Held Dispenser, IDH **2564842**
- Inlet Tube for a 250ml bottle
- Inlet Tube for a 50ml bottle (installed on pump when shipped)

#### Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

#### Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Document # 9003022, Date: 09/15/2020

Henkel Americas

1-800-LOCTITE

[www.equipment.loctite.com](http://www.equipment.loctite.com)

Henkel Europe

+49.89.320800.1800

[www.henkel.com/industrial](http://www.henkel.com/industrial)

Henkel Asia Pacific

+86.21.2891.8863

[www.henkel.com/industrial](http://www.henkel.com/industrial)

For most direct access to local support sales and technical support visit: [www.henkel.com/industrial](http://www.henkel.com/industrial)